

# BITUMEN PRIMER

Water based bituminous emulsion

## Product Uses

BITUMEN PRIMER is designed for surface priming prior to an application of water bitumen coatings.

BITUMEN PRIMER is suitable for concrete surfaces, lightweight concrete and masonry substrates.

## Technical Properties

Solid content: 35±5% w/w

Color: Brown. After drying it changes to Black

## Instructions for use

- ③ Ensure all surfaces that are to be coated are clean, free from all deleterious material and substantially free from water.  
Dampness can be tolerated.
- ③ Apply BITUMEN PRIMER after dilution 1/1 with water by a soft brush or roller to form a continuous film over the entire surface.
- ③ Quantity required: 250-300 gr./ m<sup>2</sup> ( 0.6-0.7 gal/100sq.ft ) .
- ③ Let dry for 2-24 hours, depending on ambient conditions.
- ③ Tools can be cleaned with water immediately after usage. After drying, tools should be cleaned with white spirit.

NOTE: Products health and safety data-sheet must be read and understood before use.

***For Safety detailed instructions please refer to DAYSON's safety sheets (MSDS)***

## Packaging

BITUMEN PRIMER is available in 15 kg cans.

## Storage / Precautions

Store the material in a shaded, well ventilated place.

---

## Warranty

DAYSON's products are manufactured to rigid standards of quality. DAYSON makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions DAYSON assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship.

All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.