



CE DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

No. 064/1

1. Unique identification code of the product-type :

DAYSON JOINT FLEX 7

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

Batch number : see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

Sealant for non-structural use in joints in buildings for facade elements for exterior and interior applications intended for use in cold climate

EN 15651-1 : F EXT-INT CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

AVRUPA MÜMESSİLLİK VE DIŞ TİCARET A.Ş.

Yıldız Posta Caddesi, Vefa Bey Sok Yeşil Apt B blok

No:26/12 Esentepe – İstanbul TURKEY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) :

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :



The notified body GINGER CEBTP, identification number 0074, performed the type tests and issued a test report.

8. Declared performance :

Class : 25 LM

Substrate : Mortar M1 without primer

Essential characteristics	Testing Standards	Performances	Harmonised technical specification
Reaction to fire	EN 13501-1 + A1	Class E	EN 15651-1:2012
Water tightness and air tightness			
Loss of volume	EN ISO 10563	≤ 10 %	
Resistance to flow	EN ISO 7390	≤ 3 mm	
Adhesion / Cohesion determination of tensile properties at maintained extension after immersion in water (23°C)	EN ISO 10590	NF	
Adhesion / Cohesion determination of tensile properties at -30°C	EN ISO 8339 amended	≤ 0,9 MPa	
Adhesion / Cohesion determination of tensile properties at maintained extension at -30°C	EN ISO 8340 amended	NF	
Durability	EN ISO 8340 EN ISO 9047 EN ISO 10590	Compliant	

NF : no failure

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.